

ELECTRICALLY ACTUATED CENTRIC BUTTERFLY VALVE



SPECIAL PAINTING TESTS

- ADHESION PULL-OFF TEST
- SALT CONTAMINATION TEST
- DUST CONTAMINATION TEST

AUMA Three Phase Quarter Turn Weather-Proof Actuator

<p>SIZE 250MM</p>	<p>END CONNECTION WAFER TYPE</p>	<p>PRESSURE RATING PN10</p>	<p>AIR FAIL ACTION STAY-PUT</p>
------------------------------	---	--	--

<p>VALVE MAKE & TYPE IPC - CENTRIC BUTTERFLY VALVE</p>	<p>PORT FULL BORE</p>	<p>FLOW DIRECTION BI-DIRECTIONAL</p>	<p>OPERATION ELECTRIC ACTUATOR</p>
<p>PAINT C4H AS PER ISO12944, RAL 7001</p>	<p>BODY MOC ASTM A 536 GR. 65-45-12</p>	<p>DISC MOC ASTM A 351 GR. CF8M</p>	<p>STEM MOC ASTM A 479 TP 410</p>
<p>SEAT MOC EPDM</p>	<p>FUNCTIONAL OPEARTION TIME OPENING ≤ 22 SECS CLOSING ≤ 22 SECS</p>	<p>FUNCTION (DUTY) ON-OFF</p>	<p>POWER SUPPLY 400VAC, 50Hz 3 Ph</p>