

PNEUMATICALLY ACTUATED FLOATING BALL VALVE

IBR CERTIFIED FLOATING BALL VALVE

IPC Make Flameproof
Limit Switch Box with
Position Indicator



SIZE
**(2") 50 MM/
(3") 80 MM**

CERTIFICATION
IBR

PRESSURE RATING
#150

TESTING STD.
**BSEN 12266
- PART 1**

VALVE MAKE & SERIES IPC - 402	PORT FULL BORE	DESIGN STD BSEN 17292	FACE TO FACE ASME B16.10
END CONNECTION FLANGED RF 125-250 AARH	PAINT HEAT RESISTANT ALUMINUM	BODY/TAIL PC BOLT/NOTS A193 GR B7M / A194 GR 2HM	GLAND PACKING GRAPHITE
STEM EXTENSION 100 MM	FUNCTIONAL OPEARTION TIME OPENING <4 SECS CLOSING <4 SECS	AIR FAIL POSITION CLOSE	SEAT MOC CFT
BODY MOC ASTM A 216 Gr. WCB	BALL & STEAM MOC SS 316	BODY SEAL GRAPHITE + GFT STEM SEAL GFT + VITON	FLOW DIRECTION BI-DIRECTIONAL
ACTUATOR TYPE SINGLE ACTING SPRING RETURN PNEUMATIC ACTUATOR IPCV110S FOR 50NB & IPCV125S FOR 80NB	FUNCTION (DUTY) ON-OFF	AVAILABLE CERTIFICATIONS SIL - 3 & FIRE SAFE	FIRE SAFE DESIGN CONFIRMS TO API 607