

SLEEVED PLUG VALVE



IPC Make Weatherproof
(IP67) Limit Switch Box
with Position Indicator

SIZE (6") 150 MM	SECTOR FERTILIZER INDUSTRY	PRESSURE RATING #150	TESTING STD. API 598
---	---	---------------------------------------	---------------------------------------

VALVE MAKE & TYPE IPC - SLEEVE PLUG VALVE	PORT REDUCED BORE	DESIGN STD ASME B16.34/ API 599	FACE TO FACE ASME B16.10
END CONNECTION FLANGED RF 125- 250 AARH	PAINT HEAT RESISTANT ALUMINUM PAINT	END CONNECTION STD ASME B16.5	OPERATION PNEUMATIC ACTUATOR
FUNCTION (DUTY) ON-OFF	FUNCTIONAL OPEARTION TIME OPENING <15 SECS CLOSING <15 SECS	AIR FAIL POSITION CLOSE	PLUG MOC ASTM A 351 Gr. CF3M
BODY MOC ASTM A 351 Gr. CF3M	SLEEVE MOC PTFE	ACTUATOR TYPE SINGLE ACTING SPRING RETURN PNEUMATIC ACTUATOR IPCV270S	FLOW DIRECTION BI-DIRECTIONAL