

ELECTRICALLY ACTUATED CENTRIC BUTTERFLY VALVE



SPECIAL PAINTING TESTS

- ADHESION PULL-OFF TEST
- SALT CONTAMINATION TEST
- DUST CONTAMINATION TEST

AUMA Three Phase Quarter
Turn Weather-Proof Actuator

SIZE

250MM

END CONNECTION

**WAFER
TYPE**

PRESSURE RATING

PN10

AIR FAIL ACTION

STAY-PUT

VALVE MAKE & TYPE

**IPC - CENTRIC
BUTTERFLY
VALVE**

PORT

FULL BORE

FLOW DIRECTION

BI-DIRECTIONAL

OPERATION

**ELECTRIC
ACTUATOR**

PAINT

**C4H AS PER
ISO12944, RAL
7001**

BODY MOC

**ASTM A 536 GR.
65-45-12**

DISC MOC

**ASTM A 351
GR. CF8M**

STEM MOC

**ASTM A 479
TP 410**

SEAT MOC

EPDM

FUNCTIONAL

OPERATION TIME
**OPENING ≤
22 SECS
CLOSING ≤
22 SECS**

FUNCTION (DUTY)

ON-OFF

POWER SUPPLY

**400VAC,
50Hz 3 Ph**