

# PNEUMATICALLY ACTUATED FLUSH BOTTOM BALL VALVE



IPC Make Flameproof  
Limit Switch Box with  
Position Indicator  
With Anti-Static Device  
Fire Safe Design

<b>SIZE</b> <b>300 X</b> <b>200 MM</b>	<b>DESIGN STD</b> <b>ASME</b> <b>B 16.34</b>	<b>PRESSURE RATING</b> <b>#150</b>	<b>TESTING STD.</b> <b>BS EN 12266</b> <b>PART 1 /</b> <b>API 598</b>
--	--	---------------------------------------	--

<b>VALVE MAKE</b> <b>IPC</b>	<b>VALVE TYPE</b> <b>FLUSH BOTTOM</b> <b>BALL VALVE</b>	<b>PORT</b> <b>FULL BORE</b>	<b>STEM EXTENSION</b> <b>200 MM</b>
<b>END CONNECTION</b> <b>FLANGED</b>	<b>FLOW DIRECTION</b> <b>UNI-DIRECTIONAL</b>	<b>END CONNECTION STD</b> <b>FLANGED END TO</b> <b>ASME B16.5, RF</b>	<b>OPERATION</b> <b>PNEUMATIC</b> <b>ACTUATOR</b>
<b>FUNCTION (DUTY)</b> <b>ON-OFF</b>	<b>FUNCTIONAL OPEARTION TIME</b> <b>OPENING &lt;8 SECS</b> <b>CLOSING &lt;8 SECS</b>	<b>AIR FAIL POSITION</b> <b>CLOSE</b>	<b>AIR SUPPLY PRESSURE:</b> <b>4 KG/CM<sup>2</sup></b>
<b>BODY MOC</b> <b>ASTM A 351 Gr.</b> <b>CF8</b>	<b>BALL MOC</b> <b>SS 316 (ASTM</b> <b>A351 GR. CF8M)</b>	<b>STEM MOC</b> <b>17-4PH (ASTM A564</b> <b>UNS S17400)</b>	<b>BODY PACKING</b> <b>PTFE</b>
<b>STEAM PACKING</b> <b>PTFE</b>	<b>TAIL PC BOLT/NUTS</b> <b>ASTM A 193 GR</b> <b>B7/A194 GR.2H</b>	<b>SEAT MOC</b> <b>RPTFE</b>	<b>ACTUATOR</b> <b>FLOWSERVE</b> <b>(AUTOMAX)</b> <b>SCOTCH &amp; YOKE</b>