

TRUNION MOUNTED BALL VALVE



This valve is built with a specialized seat material engineered to withstand high-temperature service and rigorously **Helium Leak Tested** for exceptional reliability.

SIZE (6") 150MM	PRESSURE RATING #600	TYPE BALL VALVE	MAKE & SERIES IPC
CONSTRUCTION TRUNION MOUNTED	END CONNECTION ASME B16.5, SMALL TONGUE & GROOVE	FACE TO FACE ASME B 16.10	SPECIAL TESTING HELIUM LEAK TEST ISO 15848 PART II
BODY MOC ASTM A351 GR CF3M	BALL MOC ASTM A351 GR CF3M	SEAT MOC RYT-PEEK-6150FE	O RING KALREZ 6375
STEM MOC ASTM A 564 T630 (A) (17-4PH)	FLOW DIRECTION BI-DIRECTIONAL	FUNCTION (DUTY) ON-OFF	ACTUATOR TYPE Scotch & Yoke Type Single Acting Actuator
BODY /STEAM PACKING GRAPHITE + RYT PEEK 6150FE	TIMING OPEN TIME < 8 SEC. CLOSE TIME < 8 SEC.	ACCESSORIES 3/2 WAY SOLENOID & FLAMEPROOF LIMIT SWITCH BOX, AFR	AIR FAIL POSITION CLOSE