

OS & Y TYPE BOLTED BONNET GATE VALVE



**EPOXY COATED (BODY
INTERNAL & DISC) GATE
VALVE**

**EPOXY COATED
(Body & Disc)**

SIZE (14") 350 MM	DESIGN STD API 600-14th EDITION	LEAKAGE CLASS API 598 - 11 EDITION	VALVE MAKE SERIES IPC GATE VALVE - 701
PRESSURE RATING CLASS 150	CONSTRUCTION OS & Y TYPE BOLTED BONNET	END CONNECTION ASME B 16.5 FERF	OPERATION GEAR OPERATED
FLOW DIRECTION BI- DIRECTIONAL	STEM / HING PIN ASTM A276 TP 410	TRIM NO. TRIM 8	SEAT MOC ASTM A516 GR.70 + ST-6 FACING
TESTING STD. API 598 - 11 Edition	FACE TO FACE. ASME B 16.10	SEAT MOC ASTM A516 Gr.70 + ST-6 Facing	BODY MOC ASTM A216 GR. WCB + (INTERNAL : EPOXY COATED)
DISC MOC ASTM A216 GR. WCB + 13% CR. FACING (EPOXY COATED - EXCEPT SEALING AREA)	STEM MOC ASTM A276 TP 410	GASKET SPW SS316 + GRAPHITE	GLAND PACKING GRAPHITE RING